Test Report for Flicker

Report ID: Strobe test
Catalog: ELED-60-xT-SLP(x=12,24 or 48)
Description: worked with regular and appropriate LED strip according to tested LED driver

Manufacturer: China Factory
Number:
Comments: 100% brightness level

Test Results

Power Supply: U=230.0V, F=50.00Hz, Voltage Modulation: No

Basic

Frequency: 100.195 Hz
Average: 6318.891 lm
Maximum: 6381.450 lm
Minimum: 6247.450 lm

IEC-Pst

PstLM: 0.018
Evaluate: Acceptable

CIE SVM

SVM: 0.030
Visibility: Not Visibile

IEEE Std 1789


NM1: 0.102
Modulation: 0.850%
NM2: 0.245
Risk Level: No Effect

ASSIST

Flicker Index: 0.002
Percent Flicker: 0.850%
Mp: 0.012
Dp: 0.386%
d : NA
a : NA
fb: NA
Evaluate: NA

CA CEC

PAM: 0.850%
PAM(40Hz): 0.044%
PAM(90Hz): 0.049%
PAM(200Hz): 0.828%
PAM(400Hz): 0.832%
PAM(1000Hz): 0.835%



Test Lab: Ecopac(UK)Power Ltd
Operator: ZL
Photometric Type: Luminous Flux
Sample Rate: 50 KS/s
Signal: P1,M6404,

Test Equipment: LFM-5000
Test Time: 2026-08-11 10:47:29
Testing Environment: 26.4 °C, 61.1%
Sample Duration: 60.0 S
According: IESNA 2000, CIE TN 006, etc

Test Report for CIE SVM


Report ID: Strobe test
Catalog: ELED-60-xT-SLP(x=12,24 or 48)
Description: worked with regular and appropriate LED strip according to tested LED driver


Manufacturer: China Factory
Number:
Comments: 100% brightness level

Test Results

Power Supply: U=230.0V, F=50.00Hz, Voltage Modulation: No
Frequency: 100.195 Hz
Maximum: 6381.450 lm
Flicker Index: 0.002
SVM: 0.030

Average: 6318.891 lm
Minimum: 6247.450 lm
Modulation: 0.850%
Visibility: Not Visibile





Test Lab: Ecopac(UK)Power Ltd
Operator: ZL
Photometric Type: Luminous Flux
Sample Rate: 50 KS/s
Signal: P1,M6404,

Test Equipment: LFM-5000
Test Time: 2026-08-11 10:47:29
Testing Environment: 26.4 °C, 61.1%
Sample Duration: 60.0 S
According: CIE TN 006:2016

Test Report for IEC Pst


Report ID: Strobe test
Catalog: ELED-60-xT-SLP(x=12,24 or 48)
Description: worked with regular and appropriate LED strip according to tested LED driver


Manufacturer: China Factory
Number:
Comments: 100% brightness level

Test Results

Power Supply: U=230.0V, F=50.00Hz, Voltage Modulation: No
Frequency: 100.195 Hz
Maximum: 6381.450 lm
Flicker Index: 0.002
PstLM: 0.018

Average: 6318.891 lm
Minimum: 6247.450 lm
Percent Flicker: 0.850%
Evaluate: Acceptable





Test Lab: Ecopac(UK)Power Ltd
Operator: ZL
Photometric Type: Luminous Flux
Sample Rate: 50 KS/s
Signal: P1,M6404,

Test Equipment: LFM-5000
Test Time: 2026-08-11 10:47:29
Testing Environment: 26.4 °C, 61.1%
Sample Duration: 60.0 S
According: IEC TR 61547-1:2020

Test Report for IEEE Std1789


Report ID: Strobe test
Catalog: ELED-60-xT-SLP(x=12,24 or 48)
Description: worked with regular and appropriate LED strip according to tested LED driver


Manufacturer: China Factory
Number:
Comments: 100% brightness level

Test Results

Power Supply: U=230.0V, F=50.00Hz, Voltage Modulation: No
Frequency: 100.195 Hz
Maximum: 6381.450 lm
Flicker Index: 0.002
NM1: 0.102, NM2: 0.245

Average: 6318.891 lm
Minimum: 6247.450 lm
Modulation: 0.850%
Risk Level: No Effect





Test Lab: Ecopac(UK)Power Ltd
Operator: ZL
Photometric Type: Luminous Flux
Sample Rate: 50 KS/s
Signal: P1,M6404,

Test Equipment: LFM-5000
Test Time: 2026-08-11 10:47:29
Testing Environment: 26.4 °C, 61.1%
Sample Duration: 60.0 S
According: IEEE Std 1789-2015