ECD24 Range

24 Watt Desk Top Range




Features :

- C8 Input
- DOE Level VI Efficiency
- Overcurrent Protection
- Short Circuit Protection
- RoHs Compliant
- 1 Year Warranty
- EN62368 Approved

Model		ECD-24-05–C8	ECD -24 -09 -C8	ECD-24-12-C8	ECD-24-24-C8
Output	DC Voltage	5vdc	9vdc	12vdc	24vdc
	Rated Current	4amp	2.6amp	2amp	1amp
	Current Range	0-4amp	0-2.6amp	0-2amp	0-1amp
	Rated Power	20 Watt	24 Watt	24 Watt	24 Watt
	Ripple & Noise	240mVp-p max	240mVp-p max	240mVp-p max	240mVp-p max
	Output Regulation	±5%	±5%	±5%	±5%
	Output Connector	2.1x5.5x12mm C+ve	2.1x5.5x12mm C+ve	2.1x5.5x12mm C+ve	2.1x5.5x12mm C+ve
Input	Voltage Range	90-264vac	90-264vac	90-264vac	90-264vac
	Frequency Range	47-63Hz	47-63Hz	47-63Hz	47-63Hz
	Input Current	1.2amp Max	1.2amp Max	1.2amp Max	1.2amp Max
	Inrush Current	40amp Max	40amp Max	40amp Max	40amp Max
	Standby Power	0.21amp Max	0.21amp Max	0.21amp Max	0.21amp Max
	Leakage Current	0.25amp Max	0.25amp Max	0.25amp Max	0.25amp Max
	Input Connector	C8	C8	C8	C8
	Operating Temp	0°C~40°C	0°C~40°C	0°C~40°C	0°C~40°C
	Cooling	Convection	Convection	Convection	Convection
Environment	Temperature Coefficient	0.05%/°C	0.05%/°C	0.05%/°C	0.05%/°C
	Humidity	5~95%RH(non-condensing)	5~95%RH(non-condensing)	5~95%RH(non-condensing)	5~95%RH(non-condensing)
	Storage Temp	-20°C~+80%°C	-20°C~+80%°C	-20°C~+80%°C	-20°C~+80%°C
Safety & EMC	Safety Standards	UL/CuL 62368-1, GS/TUV EN62368-1, SAA AN/NZ 62368.1			
	EMC Emissions	EN55032,EN55035, FCC Part 15 Class B			

MechanicalSpecification



Ecopac UK Power Ltd
Unit 4 Ridgeway
Crendon Industrial Area
Long Crendon
Buckinghamshire, HP18 9BF

www.ecopacpower.co.uk
Tel: +44 (0) 1844 204420
email :enquiry@ecopacpower.co.uk