ELED

Ecopac LED Dimmable Driver

ELED-30-DP2 Series

30W DALI 2 & Push Dimmable LED Driver

NFC Handheld devices

EasyNFC app

DALI 2

CE SELV IP20

Features:

- Constant voltage/ PWM Output (NFC regulation)
- DALI & Push dimming function (0-100%)
- AC input: 100-277VAC
- Built-in active PFC function
- Efficiency up to 83%
- Protections: Short circuit/ Over load/ Over temperature
- Cooling by free air convection
- IP20 design for indoor installation.
- Suitable for intelligent LED lighting

Models

	ELED-30-12DP2	ELED-30-24DP2
Output Specifications		
Output Voltage	12V (12-13.5V adjust by NFC)	24V (24-26V adjust by NFC)
Voltage Tolerance	± 0.5%	
Output Current	2.5A	1.25A
Rated Power	30W	
Load Regulation	± 1%	
Input Specifications		
Input Voltage	100-277VAC	
Frequency Range	47-63Hz	
Inrush Current	59A (Twidth=210μs 230VAC)	
Full Load Efficiency (Typ.)	87%	86.4%
AC Current (Max.)	0.8A	
Leakage Current	<0.50mA	
Power Factor	PF≥0.98@120VAC PF≥0.96@230VAC PF≥0.95@277VAC (Full loading)	
Protection		
Short Circuit	Constant current mode, recovers automatically after fault condition is removed	
Over Loading	≤120% constant current limiting, recovers automatically after fault condition is removed	
Over Temperature	100°C± 10°C	
Protection Class	I	
Environment		
Working Temperature	-40~+60°C (Refer to derating curve)	
Working Humidity	20-95% RH, non-condensing	

Ecopac (UK) Power Ltd
Unit 4, Ridgeway, Crendon Industrial Area
Long Crendon, Bucks, HP18 9BF

www.ecopacpower.co.uk
Tel: +44 (0) 1844 204420
Email: enquiry@ecopacpower.co.uk

ELED
Ecopac LED Dimmable Driver

ELED-30-DP2 Series

30W DALI 2 & Push Dimmable LED Driver

Safety & EMC

Storage Temperature, Humidity	-40~+80°C, 10-95% RH
Temperature Coefficient	±0.03%/°C (0-50°C)
Vibration	10-500Hz, 5G 10min./ 1 cycle, period for 60min.each along X, Y, Z axes

Safety & EMC

Safety standards	EN61347-1, EN61347-2-13, EN62493, IP20 , UL8750 (US)
Withstand voltage	I/P-O/P:3.75KVAC I/P-FG:1.88KVAC O/P-FG:0.5KVAC
Isolation resistance	I/P-O/P I/P-FG O/P-FG: 100MΩ/500VDC/25°C/70%RH
EMC Emission	Compliance to EN55015, EN61000-3-2, EN61000-3-3 (≥60% load)
EMC Immunity	Compliance to EN61000-4-2,3,4,5,6,11, EN61547

Other Specifications

Weight	0.25 Kg
Size	171.5x 54 x 20 mm
Packing	320 x 280x 215 mm (50PCS/CTN, 18 Kg/CTN))

Mechanical Specifications



Ecopac (UK) Power Ltd
Unit 4, Ridgeway, Crendon Industrial Area
Long Crendon, Bucks, HP18 9BF

www.ecopacpower.co.uk
Tel: +44 (0) 1844 204420
Email: enquiry@ecopacpower.co.uk

ELED

Ecopac LED Dimmable Driver

ELED-30-DP2 Series

30W DALI 2 & Push Dimmable LED Driver

Derating Curve



Dimming Operation

DALI Dimming Wiring Diagram1



Dimmer

DALI Dimming Wiring Diagram2



System

Ecopac (UK) Power Ltd
Unit 4, Ridgeway, Crendon Industrial Area
Long Crendon, Bucks, HP18 9BF

www.ecopacpower.co.uk
Tel: +44 (0) 1844 204420
Email: enquiry@ecopacpower.co.uk

ELED

Ecopac LED Dimmable Driver

ELED-30-DP2 Series

30W DALI 2 & Push Dimmable LED Driver

Dimming Operation

DALI Dimming Wiring Diagram3



PC+DALI Master+DIMMER

Push-Dimming Wiring Diagram1



Dimmer (with ON/OFF function)

Push-Dimming Wiring Diagram2



Dimmer

※Note: For DALI Dimming Wiring Diagram 3, please noted that only one DALI power is need in the DALI bus, so no extra DALI power is needed if the Master or Dimmer already includes the DALI Power.

Ecopac (UK) Power Ltd
Unit 4, Ridgeway, Crendon Industrial Area
Long Crendon, Bucks, HP18 9BF

www.ecopacpower.co.uk
Tel: +44 (0) 1844 204420
Email: enquiry@ecopacpower.co.uk